



# STYLE BETON

## Release Powder

<p><b>DESCRIPTION</b></p>	<p>The Style Beton Release Powder, is a dry mixture of hydrophobic powders, special ingredients and color Bayer, for use in the process of stamped concrete. The main use of this product is to prevent the adhesion of fresh concrete molds during stamping. In parallel, Release Powder Style Beton adds color variations and highlights the embossed surface, giving an attractive two-tone, in imitation of natural materials such as stone, bricks, tiles and granite.</p> <ul style="list-style-type: none"> <li>• 5 different colors are available in containers weighing 13,00 kg per piece.</li> <li>• The colors are resistant to ultraviolet rays, acids and salts.</li> <li>• Covers 80 m per container weight 13,00 kg.</li> <li>• Washed with fresh water.</li> </ul>
<p><b>Colors</b></p> <p><b>Restrictions</b></p> <p><b>Packaging</b></p> <p><b>Storage</b></p>	<p>Available in 5 colors.</p> <p>Do not apply the product of the likelihood of rain, the temperature of the substrate below 5 ° C and above 30 ° Celsius.</p> <p>13 kg</p> <p>At room temperature, in the original container. Protect from moisture.</p>
<p><b>Application</b></p>	<p>After the concrete is colored with Style Beton Color Hardener and reaches the right time for stamping the concrete surface, releasing evenly across the surface the Style Beton Release Powder. Care must be taken not to have surplus water to the</p>

	<p>surface of the concrete. This will cause lasting intense color.</p> <p>After applying the Release Powder Style Beton, following the standard procedure to stamp the concrete. Wash after two days with fresh water.</p>
<b>CLEANING</b>	<p>The stamps are recommended to be cleaned immediately after use with water and dry thoroughly before the next application</p>
<b>HEALTH AND SAFETY</b>	<p>Read the label before use .During the preparation of surfaces avoid the inhalation of dust. Use a face mask and gloves. It contains toxic.</p>
<b>GENERAL INFORMATION</b>	<p>Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.</p> <p>The information and in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.</p> <div data-bbox="858 1285 1018 1464" data-label="Image"> </div> <p style="text-align: center;"><b>STYLE BETON</b></p> <p style="text-align: center;"><b>Navarinou 8, Kalochori, Thessaloniki, Greece, 57009</b>  <b>TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832,</b>  <b>www.stylebeton.com , info@stylebeton.com</b></p>